

Report

# **Programme of Measurement of Non-Ionising Radiation emissions**

## **First Interim Report**

Document No:	03/132R
Date:	20 November 2003

An Coimisiún um Rialáil Cumarsáide Commission for Communications Regulation Abbey Court Irish Life Centre Lower Abbey Street Dublin 1 Ireland *Telephone* +353 1 804 9600 *Fax* +353 1 804 9680 *Email* info@comreg.ie *Web* www.comreg.ie

## Contents

1	Fore	word	3
2	Exec	cutive Summary	5
3	Intro	oduction	6
4	Back	ground	8
2 2 2	4.1 4.2 4.3	WHAT IS NIR? Role of the Commission for Communications Regulation The Role of Mason Communications Ltd	8 8 8
5 pro	Maso	on Communications summary report on the site measurement	
Prv	ogram	ime	10
5	ogram 5.1 5.2	INTRODUCTION	10 10 10
6	ogram 5.1 5.2 Concl	INTRODUCTION SUMMARY OF SITE REPORT RESULTS	10 10 10 31
6 An	ogram 5.1 5.2 Concl nex 1	INTRODUCTION	10 10 31 32

## **1** Foreword

The use of radio technology has played and will continue to play a significant role in the development and growth of this country. Advances in mobile radio technology with the convenience it can bring to business and consumers alike are well documented. Today in Ireland over 3.17m people own mobile phone for instance. The use of SMS messages, once the domain of the young is increasingly utilised by all ages and the latest technologies such as GPRS and now 3G with their range of new and interesting applications indicate that further growth can be anticipated in this sector.

This growth and development have raised the awareness of the public of the positive benefits mobile radio technology can bring to individuals, industry and commerce. This can be particularly important in an increasingly knowledge based economy like Ireland's where access to information and the tools to support and enhance competitiveness are key to our future progress and prosperity. To maintain this level of progress will however require continuing investment in the maintenance and upgrading of existing networks as well as the roll out of new infrastructure.

Recognising the need for this ongoing investment in infrastructure, ComReg has required that in their respective licences that all operators are compliant with the international guidelines for general exposure to electromagnetic fields. In addition to this the Commission has over the past three years published three audit reports on their compliance with emission limits for non-ionising radiation. Each audit has focused on compliance with the general exposure limits specified in the guidelines published by the International Commission on Non Ionising Radiation Protection (ICNIRP). On the basis of the work carried out in each of the audits it has been possible to confirm that all of the companies audited have procedures and processes in place to ensure compliance with these international general exposure limits.

In 2003 an extensive programme was been put in place to measure non-ionising radiation levels at up to 400 antenna sites around the country. Undertaking this programme involves measuring the highest emission level associated with each site. This work is undertaken by Mason Communications and Radio Frequency Investigations on ComReg's behalf. This data is then published as part of a process to seek to better inform the public about the 3 ComReg 03/132R compliance of radio installations with international guidelines for public exposure limits to non-ionising radiation.

This report on the first 100 sites concludes that on the basis of the audit undertaken all of the sites are significantly below the ICNIRP guideline levels. Audits continue on the remaining sites with the final report on all 400 sites due in July 2004.

## **Commission for Communications Regulation**

#### 2 Executive Summary

This report is the first of three interim reports which will outline the programme to measure Non-Ionising Radiation at 400 sites nationwide and covers the results of the first 100 sites measured under that programme. The programme has been implemented by ComReg as a result of co-operation with the Department of Communications, Marine and Natural Resources, and the Department of the Environment, Heritage and Local Government. It involves measurement of emission levels at the point of highest emission associated with antenna sites and is fully operated and funded by ComReg.

In May of 2003, following a competitive tender process, Mason Communications in conjunction with Radio Frequency Investigations were contracted by ComReg to carry out Non-Ionising Radiation emission measurements at 400 sites throughout the country. On the basis of this work, Mason have concluded that the NIR emissions from all of the 100 sites measured are significantly below the ICNIRP guideline limits<sup>1</sup>.

5

ComReg 03/132R

<sup>&</sup>lt;sup>1</sup> See Annex 1

#### 3 Introduction

The Commission for Communications Regulation (ComReg) is the licensing authority for the use of the radio frequency spectrum in Ireland. The frequency spectrum is a valuable National resource which has been used for communications purposes for over 100 years. Applications of radio spectrum, today, include the transmission of a wide range of services, including radio and television broadcasting, mobile telephony and other telecommunications services such as internet connection.

As the licensing authority for radiocommunications in Ireland, ComReg is responsible for ensuring that communications operators comply with their licence condition relating to non-ionising radiation. The radiation emissions from communications sites must be within the levels set down in the latest international guidelines.

This report represents the results of Non-Ionising Radiation measurements at the first 100 sites chosen as part of the Programme of Measurement of Non-Ionising Radiation emissions. The full programme consists of the measurement of Non-Ionising Radiation emissions at 400 sites throughout the country. The programme is being carried out by Mason Communications in conjunction with Radio Frequency Investigations on behalf of ComReg.

For each site, ComReg requires that the measured levels of non-ionising radiation emissions should not exceed the ICNIRP limits in any part of the site or surrounding area where the general public has access. This report is arranged as follows:

The first section outlines the role of the ComReg in the area of NIR. It outlines Mason Communications appointment in the programme.

The second section is Mason Communications' report on the measurement programme. It contains the summary results for each of the sites. Each site report contains a conclusion by Mason Communications on the extent of its compliance of each site with the general public exposure limits of the ICNIRP Guidelines 1998.

The third section contains the overall conclusions.

The Annex section contains two elements which are as follows:

- 1. An explanation of Non-Ionising Radiation and an explanation of the International Committee for Non-Ionising Radiation Protection and the guideline limits associated with that body.
- 2. A guide to the methodology used in the site measurements.

#### 4 Background

## 4.1 What is NIR?

Non-ionising radiation is that part of the electromagnetic spectrum below 2420 million MHz. Radio waves, infrared radiation and visible light are examples of NIR.

#### 4.2 Role of the Commission for Communications Regulation

In 2003/2004 measurements of Non-Ionising Radiation emissions are being taken at 400 sites throughout the country in a programme agreed with the Minister for Communications, Marine and Natural Resources, and the Minister for the Environment, Heritage and Local Government. The programme is being carried out by Mason Communications in conjunction with Radio Frequency Investigations (RFI) on behalf of ComReg.

The aim of the programme is to ensure that emissions from communications sites comply with the general public exposure limits set down by the International Commission for Non-Ionising Radiation Protection (ICNIRP). Some sites have been nominated by the public and the other sites are chosen by Mason/RFI, based on population coverage. Currently, radiation emissions from communications sites must be within the levels set down in the ICNIRP guidelines.

## 4.3 The Role of Mason Communications Ltd.

Following a competitive tender process held in early 2003, Mason Communications in conjunction with Radio Frequency Investigations Ltd. were chosen to carry out the site measurements. Mason Communications Ireland Ltd. is a wholly owned subsidiary of Mason Group Ltd. Mason advises many of the leading organisations in the Republic of Ireland on converging markets and converging technologies. The management of this programme by Mason Communications involved the services of Radio Frequency Investigations (RFI) Ltd. RFI has been performing Non-Ionising Radiation site surveys since its formation in 1987. RFI is accredited to ISO 17025, which ensures independence from other bodies that may be involved directly or indirectly in this programme.

# 5 Mason Communications summary report on the site measurement programme

## 5.1 Introduction

ComReg has commissioned Mason Communications, as an independent consultancy service to conduct a survey of 400 sites. Mason Communications and their measuring sub-contractor "Radio Frequency Investigation (RFI) Ltd" will work on the programme throughout 2003 and 2004.

Mason/RFI engineers measure the power density of transmissions in the various radio bands to be surveyed<sup>2</sup>. The results, derived from electric field voltage measurements, are referenced to and presented alongside the relevant International Commission on Non-Ionising Radiation Protection (ICNIRP) recommended public maximum exposure levels.

A full site report for each site is available in the Non-Ionising Radiation section of the ComReg website.

# 5.2 Summary of site report results<sup>3</sup>

<sup>&</sup>lt;sup>2</sup> See Annex 2 for the site measurement methodology

<sup>&</sup>lt;sup>3</sup> See each individual site report for the full set of measurement results

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>
	300MHz – 1GHz	9.67517E-05	4.8075
Ennis	GSM 900	0.00010391	4.7916
Garda Station	GSM 1800	7.64995E-05	9.255
	1GHz – 2GHz	7.66759E-05	9.265
	300MHz – 1GHz	0.000449426	4.5185
Kilkee	GSM 900	0.000280969	4.75135
	GSM 1800	2.78393E-07	9.16
	1GHz – 2GHz	9.15501E-07	9.19
	300MHz – 1GHz	0.000135101	4.7985
Killaloe	GSM 900	8.04746E-05	4.7939
	GSM 1800	8.388E-08	9.165
	1GHz – 2GHz	6.30462E-08	9.175
	300MHz – 1GHz	0.000211183	4.755
Kilrush	GSM 900	0.000386063	4.7398
	GSM 1800	8.34947E-09	9.38
	1GHz – 2GHz	9.80977E-09	9.44
	300MHz – 1GHz	9.54242E-05	4.79
Lahinch	GSM 900	5.85678E-05	4.78325
	GSM 1800	8.40734E-09	9.33
	1GHz – 2GHz	2.48118E-08	9.45

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m2
	300MHz – 1GHz	6.10462E-05	4.746
Newmarket on	GSM 900	6.34832E-05	4.73515
rergus	GSM 1800	9.30376E-09	9.31
	1GHz – 2GHz	8.8442E-09	9.975
	300MHz – 1GHz	0.000401475	4.746
Shannon	GSM 900	0.000231025	4.7504
	GSM 1800	5.619E-08	9.19
	1GHz – 2GHz	1.59096E-06	5.84
	300MHz – 1GHz	0.000129915	4.8075
Sixmilebridge	GSM 900	0.000138567	4.79065
	GSM 1800	9.80977E-07	9.225
	1GHz – 2GHz	7.54499E-07	9.24
	300MHz – 1GHz	4.57782E-05	3.819
Allihies	GSM 900	6.02086E-05	4.743
	GSM 1800	1.81409E-08	9.195
	1GHz – 2GHz	2.5215E-06	7.515
	300MHz – 1GHz	0.000191716	2.41
Bandon	GSM 900	5.30467E-05	4.743
	GSM 1800	1.3233E-08	9.2
	1GHz – 2GHz	1.21803E-08	9.25

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>
	300MHz – 1GHz	4.99642E-05	4.2475
Bandon	GSM 900	3.77276E-05	4.7703
Garda Station	GSM 1800	0.000317438	9.235
	1GHz – 2GHz	0.00024359	9.265
	300MHz – 1GHz	0.000474962	3.53
Bantry	GSM 900	3.85175E-05	4.79575
	GSM 1800	1.76872E-08	9.09
	1GHz – 2GHz	2.22156E-08	6.665
	300MHz – 1GHz	0.001144613	4.7635
Buttevant	GSM 900	0.000928237	4.74115
	GSM 1800	9.92336E-09	9.105
	1GHz – 2GHz	1.44763E-08	9.5
	300MHz – 1GHz	6.5563E-05	4.7985
Castletown	GSM 900	6.57141E-05	4.7814
	GSM 1800	6.07657E-08	9.09
	1GHz – 2GHz	4.57782E-08	8.15
	300MHz – 1GHz	0.00051128	4.711
Charleville	GSM 900	0.000518392	4.7023
	GSM 1800	8.29199E-09	9.395
	1GHz – 2GHz	9.09198E-09	9.69

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>
	300MHz – 1GHz	0.000136038	4.7725
Cloyne	GSM 900	0.000111086	4.7953
	GSM 1800	4.34169E-08	9.165
	1GHz – 2GHz	4.97346E-08	9.175
	300MHz – 1GHz	0.001010785	4.8075
Gaggin	GSM 900	0.000629012	4.7939
	GSM 1800	1.09562E-08	9.385
	1GHz – 2GHz	3.39358E-08	8.09
	300MHz – 1GHz	0.000219613	4.816
Glanmire,	GSM 900	0.000212647	4.7976
Glasnadoy	GSM 1800	0.000282266	9.27
	1GHz – 2GHz	0.000214614	9.265
	300MHz – 1GHz	0.000256247	4.7635
Inishannon	GSM 900	0.000238594	4.75275
	GSM 1800	1.65447E-08	9.36
	1GHz – 2GHz	1.79332E-07	5.325
	300MHz – 1GHz	0.000620381	4.746
Kanturk	GSM 900	0.000270806	4.7324
	GSM 1800	9.19726E-09	9.345
	1GHz – 2GHz	9.90053E-09	9.115

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>
	300MHz – 1GHz	0.000110321	4.7635
Killeagh	GSM 900	0.00011552	4.7444
	GSM 1800	1.88651E-08	9.35
	1GHz – 2GHz	1.1958E-07	9.45
	300MHz – 1GHz	4.53585E-05	4.781
Kilpatrick	GSM 900	5.67099E-05	4.7615
	GSM 1800	1.9349E-08	9.17
	1GHz – 2GHz	1.7728E-08	9.925
	300MHz – 1GHz	0.001366654	4.72
Kinsale	GSM 900	0.001732442	4.70415
	GSM 1800	6.42183E-08	9.235
	1GHz – 2GHz	8.14064E-08	9.25
	300MHz – 1GHz	0.000449426	4.781
Mallow	GSM 900	0.000404258	4.7606
	GSM 1800	0.000737324	9.16
	1GHz – 2GHz	0.000541575	9.19
	300MHz – 1GHz	6.69358E-05	4.79
Mayfield,St.	GSM 900	4.08939E-05	4.7953
John's National School	GSM 1800	1.63177E-05	9.165
SCN001	1GHz – 2GHz	1.89522E-05	9.175

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>
	300MHz – 1GHz	0.000292185	4.711
Midleton	GSM 900	0.000360295	4.7
	GSM 1800	0.000520785	9.19
	1GHz – 2GHz	0.000220627	9.2
	300MHz – 1GHz	0.000526816	4.7285
Ovens	GSM 900	0.001100674	4.71575
	GSM 1800	1.28428E-06	9.21
	1GHz – 2GHz	1.44098E-06	9.225
	300MHz – 1GHz	0.001123721	4.7635
Rosscarbery	GSM 900	0.000400552	4.7504
	GSM 1800	2.49263E-08	9.085
	1GHz – 2GHz	1.7728E-08	9.825
	300MHz – 1GHz	0.000343288	4.816
Struake	GSM 900	0.000156192	4.7985
Donougnmore	GSM 1800	7.72074E-08	9.16
	1GHz – 2GHz	6.86529E-08	9.19
	300MHz – 1GHz	0.002803229	4.79
Timoleague	GSM 900	0.002683235	4.7726
rarmyara	GSM 1800	9.21847E-09	9.14
	1GHz – 2GHz	9.09198E-09	9.9

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m2
	300MHz – 1GHz	4.24286E-05	4.7635
Timoleague	GSM 900	5.34144E-05	4.73285
	GSM 1800	8.42672E-09	9.39
	1GHz – 2GHz	1.17668E-08	9.265
	300MHz – 1GHz	0.00273312	4.72
Watergrasshill	GSM 900	0.003255807	4.7097
	GSM 1800	4.29199E-08	9.205
	1GHz – 2GHz	2.95569E-07	5.44
	300MHz – 1GHz	0.000442241	4.711
Youghal	GSM 900	0.000552915	4.7532
	GSM 1800	0.000364467	9.165
	1GHz – 2GHz	0.00036615	9.19
	300MHz – 1GHz	0.000526816	4.79
Bagenalstown	GSM 900	0.000337799	4.7962
	GSM 1800	1.02958E-08	9.16
	1GHz – 2GHz	2.44151E-08	7.55
	300MHz – 1GHz	0.000182246	4.755
Carlow Town	GSM 900	0.000361126	4.7435
	GSM 1800	3.01758E-05	9.165
	1GHz – 2GHz	0.000565794	9.2

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m2
	300MHz – 1GHz	2.64033E-05	2.5675
Leighlinbridge	GSM 900	2.94211E-05	4.76105
	GSM 1800	8.33026E-08	9.165
	1GHz – 2GHz	8.90551E-08	9.2
	300MHz – 1GHz	0.000501948	4.7985
Rathvilly	GSM 900	0.000482679	4.78835
	GSM 1800	3.47263E-08	9.18
	1GHz – 2GHz	2.97618E-08	5.74
	300MHz – 1GHz	0.000722202	4.79
Tullow	GSM 900	0.000661696	4.76985
	GSM 1800	1.01311E-08	9.3
	1GHz – 2GHz	5.19587E-08	9.44
	300MHz – 1GHz	0.000458837	4.755
Athenry	GSM 900	0.000424286	4.7384
	GSM 1800	9.17611E-09	9.095
	1GHz – 2GHz	2.82917E-08	9.475
	300MHz – 1GHz	0.000639232	4.7985
Ballinasloe	GSM 900	0.000148819	4.7976
	GSM 1800	6.26122E-07	9.16
	1GHz – 2GHz	4.55679E-07	9.175

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m2
	300MHz – 1GHz	0.000125216	4.781
Cong,	GSM 900	0.00010781	4.7615
Asniord Castle	GSM 1800	8.90551E-09	9.05
	1GHz – 2GHz	9.26102E-09	9.825
	300MHz – 1GHz	0.001886508	4.7985
Craughwell	GSM 900	0.001869212	4.7814
	GSM 1800	8.8442E-09	9.09
	1GHz – 2GHz	9.96916E-09	9.9
	300MHz – 1GHz	0.000126666	4.72
Gort	GSM 900	9.58647E-05	4.7014
	GSM 1800	1.69301E-08	9.2
	1GHz – 2GHz	1.25504E-08	9.69
	300MHz – 1GHz	0.000227331	4.781
Inverin	GSM 900	0.000229963	4.76015
	GSM 1800	8.86459E-09	9.12
	1GHz – 2GHz	1.29915E-08	6.015
	300MHz – 1GHz	0.000441224	4.72
Kilcolgan	GSM 900	0.000474962	4.7065
	GSM 1800	4.22337E-08	9.215
	1GHz – 2GHz	4.32174E-07	8.99

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m2
	300MHz – 1GHz	0.000198911	4.7635
Loughrea	GSM 900	0.000186491	4.74395
	GSM 1800	9.34671E-09	9.36
	1GHz – 2GHz	1.00846E-08	9.325
	300MHz – 1GHz	0.000269562	4.781
Oranmore	GSM 900	0.000210213	4.76105
	GSM 1800	1.08308E-08	9.225
	1GHz – 2GHz	5.63195E-08	5.25
	300MHz – 1GHz	0.000240801	4.72
Spiddal West	GSM 900	0.000217099	4.7356
	GSM 1800	9.69747E-09	9.32
	1GHz – 2GHz	5.20785E-08	9.44
	300MHz – 1GHz	3.85175E-05	4.746
Tuam	GSM 900	3.39358E-05	4.73005
	GSM 1800	3.75542E-05	9.17
	1GHz – 2GHz	4.84907E-05	8.7
	300MHz – 1GHz	0.000282266	4.755
Callan	GSM 900	0.000342498	4.72685
	GSM 1800	9.85505E-09	9.15
	1GHz – 2GHz	4.02401E-08	9.5

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>	
	300MHz – 1GHz	7.22202E-05	4.781	
Castlecomer	GSM 900	6.58656E-05	4.7555	
	GSM 1800	9.02939E-09	9.33	
	1GHz – 2GHz	4.98493E-08	9.49	
	300MHz – 1GHz	0.000296933	4.8075	
Goresbridge	GSM 900	0.000198453 4.77865	4.77865	
	GSM 1800	9.47673E-09	9.14	
	1GHz – 2GHz	3.74678E-08	9.45	
	300MHz – 1GHz	0.00019528	4.7635	
Inistoge	Inistoge GSM 900 0.00017	0.000177688	4.7361	
	GSM 1800 8.72285E-09		9.18	
	1GHz – 2GHz	1.21523E-08	6.015	
	300MHz – 1GHz	0.000279678	4.781	
Kilkenny City	GSM 900	0.000234239	4.75735	
	GSM 1800	0.000361958	9.225	
	1GHz – 2GHz	0.000232091	9.25	
	300MHz – 1GHz	0.001013115	4.7285	
Knocktopher	GSM 900	0.001329409	4.7037	
	GSM 1800	9.21847E-09	9.26	
	1GHz – 2GHz	9.54242E-09	9.675	

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>	
	300MHz – 1GHz	0.000154049	2.349	
Cahirciveen	GSM 900	1.18757E-05	4.79805	
	GSM 1800	1.82666E-08	9.15	
	1GHz – 2GHz	4.00552E-05	7.565	
	300MHz – 1GHz	0.00160938	4.8075	
Cappaclough	GSM 900	0.001797458	4.78835	
	GSM 1800	1.86921E-08	9.195	
	1GHz – 2GHz	1.65828E-08	9.7	
	300MHz – 1GHz	0.001732442	4.781	
Castleisland	eisland GSM 900 0.001522855	4.74165		
	GSM 1800	1.94383E-08	9.35	
	1GHz – 2GHz	3.33164E-08	9.49	
	300MHz – 1GHz	0.001404943	4.781	
Dingle	GSM 900	0.001229302	4.76015	
	GSM 1800	4.45306E-08	9.16	
	1GHz – 2GHz	3.68688E-08	9.19	
	300MHz – 1GHz	9.30376E-05	4.5625	
Glenbeigh	GSM 900	6.97684E-05	4.7296	
	GSM 1800	1.78508E-08	9.28	
	1GHz – 2GHz	1.92601E-08	9.465	

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>	
	300MHz – 1GHz	0.000116589	4.7635	
Killarney	GSM 900	0.000108557	4.743	
	GSM 1800	1.76059E-08	9.055	
	1GHz – 2GHz	1.86491E-08	9.865	
	300MHz – 1GHz	0.000406124	4.816	
Killorglin	GSM 900	0.000368688 4.7948	4.7948	
	GSM 1800	1.79746E-08	9.23	
	1GHz – 2GHz	1.76465E-08	9.9	
	300MHz – 1GHz	0.000541575	4.79	
Rathmore	GSM 900	0.000551644	4.77125	
	GSM 1800	GSM 1800 1.74847E-08		
	1GHz – 2GHz	1.96182E-08	9.775	
	300MHz – 1GHz	0.000514824	4.7635	
Slieve Mish	GSM 900	0.00052803	4.74855	
	GSM 1800	2.61613E-07 9.21		
	1GHz – 2GHz	7.66759E-06	6.925	
	300MHz – 1GHz	0.001070677	4.755	
Tralee	GSM 900	0.000639232	4.7333	
	GSM 1800	0.001182112	9.165	
	1GHz – 2GHz	0.00120132	9.215	

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>	
	300MHz – 1GHz	5.05427E-06	4.7635	
Ventry	GSM 900	3.99631E-06	4.7407	
	GSM 1800	1.92158E-08	9.21	
	1GHz – 2GHz	2.70183E-08	6.015	
	300MHz – 1GHz	0.007155808	4.8075	
Waterville	GSM 900	0.005329159	4.78605	
	GSM 1800	2.05428E-08	9.335	
	1GHz – 2GHz	1.88217E-08	9.54	
	300MHz – 1GHz 0.000793		4.545	
Abbeyleix	GSM 900	8.8442E-05	4.77495	
	GSM 1800	1.09058E-08	9.235	
	1GHz – 2GHz	1.86921E-08	9.5	
	300MHz – 1GHz	0.000437178	4.755	
Durrow	GSM 900	0.000452542	4.7518	
	GSM 1800	9.54242E-09	9.125	
	1GHz – 2GHz	1.03671E-08	9.09	
	300MHz – 1GHz	0.000235862	4.8075	
Portarlington	GSM 900	0.000194831	4.78235	
	GSM 1800	3.79017E-08 9.195		
	1GHz – 2GHz	5.21986E-08	9.225	

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>	
	300MHz – 1GHz	6.10462E-05	4.8075	
Portlaoise	GSM 900	3.52906E-05	4.78	
	GSM 1800	8.46562E-05	9.205	
	1GHz – 2GHz	0.000151586	9.24	
	300MHz – 1GHz	0.000559318	3.1365	
Achill Sound	GSM 900	0.000265863	4.7472	
	GSM 1800	1.09814E-08	9.315	
	1GHz – 2GHz	3.24085E-05	7.6	
	300MHz – 1GHz	3.8785E-05 4.825		
Ballina	Ballina GSM 900	5.1959E-05	4.79945	
	GSM 1800	1.4311E-07	9.19	
	1GHz – 2GHz	2.2891E-07	9.225	
	300MHz – 1GHz	0.000652617	4.7985	
Ballycastle	GSM 900	0.000558031	4.7777	
	GSM 1800	9.47673E-09	9.14	
	1GHz – 2GHz	1.10575E-08	9.79	
	300MHz – 1GHz	0.001624272	4.7725	
Belmullet	GSM 900	0.001474547	4.75225	
	GSM 1800	8.42672E-09	9.405	
	1GHz – 2GHz	GHz – 2GHz 5.84331E-08		

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>	
	300MHz – 1GHz	4.91653E-06	4.781	
Castlebar	GSM 900	1.08308E-06	4.76105	
	GSM 1800	1.61309E-06	9.175	
	1GHz – 2GHz	3.99631E-07	9.2	
	300MHz – 1GHz	0.000279678	4.7725	
Louisberg	GSM 900	0.000432174 4.76015	4.76015	
	GSM 1800	8.78332E-09	9.225	
	1GHz – 2GHz	1.02958E-08	9.85	
	300MHz – 1GHz	0.000784619	4.7635	
Westport	GSM 900	0.000759729	4.7435	
	GSM 1800	1.13412E-05	9.185	
	1GHz – 2GHz	0.000505427	8.75	
	300MHz – 1GHz	0.001017791	4.781	
Birr	GSM 900	0.001090583	4.75965	
	GSM 1800	0.000333932	9.165	
	1GHz – 2GHz	0.000463083	9.19	
	300MHz – 1GHz	0.000996916	4.7725	
Clara	GSM 900	0.000969747	4.7532	
	GSM 1800	1.02721E-08	9.405	
	1GHz – 2GHz	1.05599E-08	9.515	

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m <sup>2</sup>	
	300MHz – 1GHz	0.00031817	4.7725	
Daingean	GSM 900	0.000337799	4.75225	
	GSM 1800	2.41356E-08	9.17	
	1GHz – 2GHz	2.75206E-08	9.24	
	300MHz – 1GHz	0.000980977	4.7635	
Tullamore	GSM 900	0.000952048 4.73795	4.73795	
	GSM 1800	6.99292E-06	9.18	
	1GHz – 2GHz	8.70279E-06	9.2	
	300MHz – 1GHz	0.001027209	4.711	
Birdhill	GSM 900	0.000773853	4.6949	
	GSM 1800	0.000643663	9.23	
	1GHz – 2GHz	0.000487145	9.25	
	300MHz – 1GHz	0.001801601	4.7725	
Cahir	GSM 900	0.001385666	4.7458	
	GSM 1800	8.19707E-09	9.33	
	1GHz – 2GHz	1.62427E-07	9.515	
	300MHz – 1GHz	0.00076148	4.7725	
Cashel	GSM 900	0.000858339	4.7546	
	GSM 1800	1.29616E-08	9.18	
	1GHz – 2GHz	9.54242E-09	8.85	

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m2	
	300MHz – 1GHz	0.00088442	4.7635	
Clonmel	GSM 900	0.000681803	4.76105	
	GSM 1800	0.000272683	9.16	
	1GHz – 2GHz	0.00059932	9.175	
	300MHz – 1GHz	0.000264642	4.7285	
Nenagh	GSM 900	0.000486025 4.710	4.7107	
	GSM 1800	0.001269576	9.195	
	1GHz – 2GHz	0.000888502	9.215	
	300MHz – 1GHz	0.00024359	4.571	
Thurles	s GSM 900 6.70901E-05	6.70901E-05	4.7421	
	GSM 1800	0.000137613	9.16	
	1GHz – 2GHz	0.000189086	9.215	
	300MHz – 1GHz	0.000210697	4.755	
Tipperary	GSM 900	0.000223696	4.73795	
Town	GSM 1800	2.83569E-07	9.16	
	1GHz – 2GHz	2.53314E-07	9.19	
	300MHz – 1GHz	0.00491653	4.79	
Toomeyvara	GSM 900	0.005101039	4.76615	
	GSM 1800	4.69525E-08	9.23	
	1GHz – 2GHz	3.10212E-08	9.19	

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m2	
	300MHz – 1GHz	0.000210697	4.781	
Dungarvan	GSM 900	0.000241913	4.75645	
	GSM 1800	2.86193E-05	9.16	
	1GHz – 2GHz	2.56838E-05	9.19	
	300MHz – 1GHz	0.001414681	4.781	
Kilmacthomas	GSM 900	0.001272503	4.75965	
	GSM 1800	9.76469E-09	9.245	
	1GHz – 2GHz	1.10321E-08	9.2	
300MHz – 1GHz		0.000102249	4.7725	
Kilmeaden	GSM 900	8.388E-05	4.75225	
	GSM 1800	3.00371E-07	9.33	
	1GHz – 2GHz	2.36951E-07	9.365	
	300MHz – 1GHz	0.002408012	4.79	
Lismore	GSM 900	0.001139354	4.76615	
	GSM 1800	1.36038E-09	9.3	
	1GHz – 2GHz	3.46464E-09	6.015	
	300MHz – 1GHz	0.000440209	4.7635	
Tramore	GSM 900	0.000629012	4.73745	
	GSM 1800	0.001526366	9.17	
	1GHz – 2GHz	1GHz – 2GHz 0.001681352		

Site	Frequency Range	Highest reading W/m <sup>2</sup>	ICNIRP guideline Limit W/m2	
	300MHz – 1GHz	0.001366654	4.79	
Ardkeen	GSM 900	0.001519353	4.7657	
	GSM 1800	0.001434362	9.195	
	1GHz – 2GHz	0.001176681	9.275	
	300MHz – 1GHz	0.00036784	4.72	
Ferrybank	GSM 900	0.000342498 4.6977	4.6977	
	GSM 1800	0.000335474	9.2	
	1GHz – 2GHz	0.000340925	9.225	
	300MHz – 1GHz 0.00231557		4.781	
Kilcohan	GSM 900	SM 900 0.002068515	4.762	
	GSM 1800	0.002242119	9.19	
	1GHz – 2GHz	0.002720562	9.215	
	300MHz – 1GHz	0.000168135	4.79	
Waterford City	GSM 900	0.000171261	4.76615	
	GSM 1800	0.000252731	9.275	
	1GHz – 2GHz	0.000313082	9.3	
	300MHz – 1GHz		4.545	
Laragh	GSM 900	0.002299634	4.74855	
	GSM 1800	2.27331E-08	9.26	
	1GHz – 2GHz	2.11183E-08	9.94	

# **6** Conclusion

The conclusion of the audits undertaken is that emission levels at all the sites measured fall significantly below the International ICNIRP general exposure levels. In the vast majority of cases the levels are in fact less than one ten-thousandth of the ICNIRP limits.

## Annex 1

# Non-Ionising Radiation (NIR) and the International Commission for Non-Ionising Radiation Protection (ICNIRP)

Definition

Non-ionising radiation is that part of the electromagnetic spectrum below 2420 million MHz. Radio waves, infrared radiation and visible light are examples of NIR. Electromagnetic waves at frequencies above 2420 million MHz (2.4THz) are known as ionising radiation and this includes X-rays and Gamma rays.

Standards for emissions limits for non-ionising radiation

The International Commission for Non-Ionising Radiation Protection (ICNIRP) is an independent, scientific organisation established in 1992. The ICNIRP was established for the purpose of advancing Non-Ionising Radiation Protection for the benefit of people and the environment and in particular to provide guidance and recommendations on protection from NIR exposure. ICNIRP operates in co-operation with the Environmental Health Division of the World Health organisation and the United Nations Environment Programme. In 1998 ICNIRP issued a position paper on the health and safety aspects of NIR. This reviewed both thermal and athermal effects and its conclusion endorsed the 1988 guidelines produced by the International Radiation Protection Association (IRPA).

This programme required sites to be in compliance with the ICNIRP (1998) guidelines. A summary of the maximum public exposure levels in the ICNIRP Guidelines for the radio systems in this audit are shown in Table 1. It should be noted that in 1999 the European Commission issued a recommendation<sup>4</sup> which proposed to limit exposure of the general public to electromagnetic fields 0Hz - 300GHz based on a set of basic restrictions and reference levels developed internationally under the advice of the

<sup>&</sup>lt;sup>4</sup> Recommendation of the European Council 1999/519/EC of July 12, 1999

International Commission on Non-Ionising Radiation Protection. In relation to emissions within the radio spectrum, these limits are equivalent to the ICNIRP guideline limits used by ComReg.

## ICNIRP limits

In 1998 ICNIRP produced "Guideline for Limiting Exposure to Time-Varying Electric, Magnetic and Electromagnetic Fields (up to 300 GHz)". ComReg and a large number of international regulators have adopted the 1998 ICNIRP document as the reference for ensuring that NIR levels do not cause an adverse health effect.

The main purpose of the "Guideline for Limiting Exposure to Time-Varying Electric, Magnetic and Electromagnetic Fields (up to 300 GHz)" is to provide guidelines for limiting Electromagnetic Field (EMF) exposure that will provide protection against known adverse health effects. An adverse health effect causes detectable impairment of the health of the exposed individual or his or her offspring.

Two classes of guidance are presented:

- Basic Restrictions
- Reference Levels

## **Basic Restrictions**

Restrictions on exposure to time-varying electric, magnetic and electromagnetic fields that are based on health effects are termed "basic restrictions". Depending upon the frequency of the field, the physical quantities used to specify these restrictions are current density (J), Specific Absorption Rate (SAR), and power density (S).However, only power density in air, outside the body, can be readily measured in exposed individuals.

## Reference Levels

These levels are provided for practical exposure assessment purposes to determine whether the basic restrictions are likely to be exceeded. Some reference levels are derived from basic restrictions using measurement and/or computational techniques, and some address perception and adverse indirect effects of exposure to EMF.

Compliance with the reference levels will ensure compliance with the relevant basic restriction. If the measured or calculated value exceeds the reference level, it does not necessarily follow that the basic restriction will be exceeded. However, when a reference level is exceeded, it is necessary to test compliance with the relevant basic restriction and to determine whether additional protective measures are necessary.

The ICNIRP Guidelines: 1998 reference levels appropriate to the frequency range 100 kHz to 40GHz, covered by this report are given in the table on the following page.

# GUIDELINE LIMITS OF NIR FOR MEMBERS OF THE GENERAL PUBLIC

Frequency	Unperturbed RMS	Unperturbed RMS	Equivalent Plane	Radio Service
f (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength H (A/m)	Wave Power Density (mW/cm <sup>2</sup> )	
0.003-0.15	87	5	-	
0.15-1	87	0.73/f	-	LW and MW Radio Broadcasting
1-10	87/f <sup>1/2</sup>	0.73/f	-	
10-400	28	0.073	02	VHF Radio and Television
400-2000	1.375f <sup>1/2</sup>	0.0037f <sup>1/2</sup>	f/2000	Broadcasting UHF Television Broadcasting and Mobile Telephony
2000-300000	61	0.16	1	Microwave Links, and MMDS

The guideline levels are lowest in the 10 MHz to 400 MHz frequency range as at these wavelengths resonance in parts or all of the body may occur resulting in optimum coupling of the radio frequency energy.

The ICNIRP guidelines require that in instances of simultaneous exposure to multiple sources, the sum of the exposure levels should be considered. In the case of the frequency range 30 MHz to 40 GHz, covered by the narrowband equipment used to generate this report, both the electric field strength and the magnetic field strength at each frequency should be expressed as a fraction of

the limit at that frequency and both the sum of the electric field strength fractions squared and the sum of the magnetic field strength fractions squared should not exceed unity.

## Annex 2

## Methodology and measurements

## Introduction

Measurements of the non-ionising radiation emissions from each site were conducted, in accordance with ECC Recommendation (02) 04. For the purposes of this programme, measurements were carried out at GSM sites and Mixed Use sites.

## Cellular/GSM sites

Cellular/GSM Sites are sites and locations in Ireland at which electronic communications network transmission facilities and/or infrastructure are located, the primary purpose or sole use of such facilities/infrastructure being to facilitate the provision of mobile telephony services in Ireland.

## Mixed use site

Mixed use sites are sites and locations in Ireland at which electronic communications network transmission facilities and/or infrastructure are located and where such facilities and or infrastructure is not primarily or solely used to facilitate the provision of mobile telephone services in Ireland.

## Methodology

An initial survey of the area was conducted to determine the location(s) of highest non-ionising radiation emissions. At the GSM only site this was done by using a broadband probe and an engineering mobile phone, in conjunction with the appropriate software, to identify the position of maximum field strength. The engineering mobile phone provides an indication of the field strength levels from the GSM channels in use in the vicinity of the site.

Once the locations of the highest field strength emissions were identified, a series of narrowband measurements were taken at these locations. These measurements were taken using a spectrum analyser and associated antennas.

At GSM only sites, measurements were performed over the following frequency range from 300MHz - 2GHz. This range includes both the GSM900 and GSM1800 bands.

For mixed use sites, measurements were performed over the following frequency ranges 30MHz – 40GHz. These measurements included all radio services which are present at these sites. These services include, GSM, Broadcasting, fixed links, MMDS, FWA. Point to Point links, amongst others.

At both GSM only sites and Mixed Use sites, electric field strength measurements conducted in the frequency bands of interest, are recorded and converted to power density levels for direct comparison with the ICNIRP guideline levels. These power density levels are tabulated alongside the relevant ICNIRP limits. The tables present the highest emission level readings recorded within a band.